



## Airhandlers

### LU05BE Airhandler

Low-noise water-cooled ventilation unit with a 50 kW cooling capacity, fitted with continuously variable ventilation control that can blow in three directions. The airhandler is equipped with an extra defrost element which makes it also suitable for low temperature applications. For electrical defrosting a 32 A CEE connection is required. The unit is equipped with a condensate pump, ready for connection and easy to install by using shortcuts. The unit is easy to move with a pallet cart or forklift.

#### Technical specifications **LU05BE**

Cooling capacity <sup>1</sup>	50 kW	External (Air) pressure <sup>1</sup>	300 Pa	Height <sup>2</sup>	2250 mm
Cooling capacity	50 kW	Voltage <sup>1</sup>	230 V	Weight <sup>2</sup>	475 kg
Current (nominal)	7.5 A	Phases <sup>2</sup>	3 + N + A	Sound level (at 10 m) <sup>3</sup>	45 dB(A)
Capacity steps	Frequentie geregeld	Length <sup>2</sup>	1620 mm		
Max. air flow <sup>1</sup>	7500 m <sup>3</sup> /h	Width <sup>2</sup>	780 mm		

<sup>1</sup> Cooling: Water 6 - 12 °C, air 30 °C / 60% RV

<sup>2</sup> Maximum heating capacity 75 kW

<sup>3</sup> Without top box 1620 x 780 x 1900