



Shockfreezers

MI01B Freezer unit

Representative, low-energy and low-noise cell constructed in accordance with HACCP & GMP requirements, with a volume of 25 m³. Especially developed for shock freezing / blast chilling of products. Ready for use and easy to install with a crane truck, even in locations that are difficult to reach. Can be used both outdoors and indoors. Equipped with low GWP refrigerant. Accessible via door that can also be opened from the inside. Including LED lighting.

Technical specifications **MI01B**

Amount of pallets (euro) ¹	10	Current (nominal) ⁴	38 A	Height (internal) ⁴	1970 mm
Min. inside temperature ²	-35 °C	Phases ⁴	3 + N + A	Door height ⁴	2100 mm
Max. inside temperature ²	5 °C	Length (external) ⁴	6450 mm	Door width ⁴	1400 mm
Min. outside temperature ² °C		Width (external) ⁴	2950 mm	Weight ⁴	3500 kg
Max. outside temperature ² °C		Height (external) ⁴	2930 mm	Sound level (at 10 m) ⁴	59 dB(A)
Voltage ³	400 V	Length (internal) ⁴	4700 mm		
Current (max) ⁴	59.5 A	Width (internal) ⁴	2700 mm		

¹ Without top box 1620 x 780 x 1900

² After approval of Coolworld International

³ Maximum heating capacity 75 kW

⁴ With electrical heating