Coolw®rld



Freezer containers

RU40B Ultra Low Freezing container

Robust Cool-Freezing container (40-ft reefer high cube) with a capacity of 57 m³. Especially developed for ultralow temperatures down to -70 °C. The container is provided with an aluminum T-section floor, stainless steel interior and special doors. The standard container does not meet HACCP / GMP requirements. Can optionally be configured with remote monitoring, refrigerated anteroom and lighting

Technical specifications **RU40B**

Amount of pallets (euro) 1	21	Current (nominal) ¹	26 A	Height (internal) 1	2420 mm
Min. inside temperature ²	-70 °C	Phases ¹	3 + A	Door height ¹	1600 mm
Max. inside temperature ²	-10 °C	Length (external) 1	12192 mm	Door width ¹	2100 mm
Min. outside temperature ²	-30 °C	Width (external) 1	2440 mm	Sound level (at 10 m) ¹	64 dB(A)
Max. outside temperature ²	50 °C	Height (external) ¹	2896 mm	Weight ¹	6210 kg
Voltage ³	400 V	Length (internal) ¹	11269 mm		
Current (max) 1	31 A	Width (internal) ¹	2088 mm		

¹ With electrical heating

² After approval of Coolworld International

³ Maximum heating capacity 75 kW