




Freezer rooms

MV02 Freezer unit

Ready-for-use mobile freezer unit with a volume of 100 m³ and a large freezing overcapacity (temperature range down to minus 35 °C*). The frozen storage cell has been fitted with a flat anti-skid floor, lighting, a door with frame heating that opens smoothly (also from the inside), and has a very low entry height. The frozen storage cell meets the HACCP/GMP requirements, and standard features include a data log system. The unit is easy to install with a crane truck. This storage cell is low noise and low energy.

Technical specifications MV02



Amount of pallets (euro) ¹	28	Current (nominal) ¹	14.8 A	Width (internal) ¹	3200 mm
Min. inside temperature ²	-35 °C	Recommended fuses ¹	25 A	Height (internal) ¹	2700 mm
Max. inside temperature ²	2 °C	Phases ¹	3 + N + A	Door height ¹	2500 mm
Min. outside temperature ²	-20 °C	Length (external) ¹	12000 mm	Door width ¹	2000 mm
Max. outside temperature ²	37 °C	Width (external) ¹	3500 mm	Weight ¹	6700 kg
Voltage ³	400 V	Height (external) ¹	3000 mm	Sound level (at 10 m) ¹	50 dB(A)
Current (max) ¹	21 A	Length (internal) ¹	10500 mm		

¹ With electrical heating

² After approval of Coolworld International

³ When additional reheating is utilised

