



Refrigerated containers

RF20 Refrigeration/freezer container

Robust refrigeration/freezer container (20-ft reefer) with a volume of 28 m³. The container features an aluminium T-profile floor, SST inner lining and double doors. The container can be moved with contents with the use of a forklift or crane truck. The container does not meet the HACCP/GMP requirements.

Technical specifications RF20

Amount of pallets (euro) ¹	10	Recommended fuses ¹	25 A	Door height ¹	2200 mm
Min. inside temperature ²	-25 °C	Phases ¹	3 + A	Door width ¹	2260 mm
Max. inside temperature ²	25 °C	Length (external) ¹	6060 mm	Treshold height, min. ¹	210 mm
Max. outside temperature ²	38 °C	Width (external) ¹	2440 mm	Treshold height, max. ¹	270 mm
Min. outside temperature ²	-20 °C	Height (external) ¹	2590 mm	Weight ¹	3400 kg
Voltage ³	400 V	Length (internal) ¹	5450 mm	Sound level (at 10 m) ¹	58 dB(A)
Current (max) ¹	19.5 A	Width (internal) ¹	2280 mm		
Current (nominal) ¹	16.3 A	Height (internal) ¹	2260 mm		

¹ With electrical heating

² After approval of Coolworld International

³ When additional reheating is utilised